



NOTES:

DETAIL REPRESENTS 1-1/2" SERVICE CONNECTION TO MAIN FOR TWO LOTS:

1. USE FORD SERIES S91 BRONZE SADDLE SERVICE CLAMP AND A BRASS COMPRESSION x MIPT ADAPTER. A RIGID LINER SHALL BE USED INSIDE OF TUBING AT THE COMPRESSION FITTINGS.
2. ALL FITTINGS SHALL BE COMPATIBLE WITH SERVICE SIZE.
3. SERVICE LINE INSTALLATION AT AN EXISTING CURB & GUTTER AND SIDEWALK WITH PLANTER STRIP SHALL HAVE THE UTILITY BOX LOCATED IN THE CENTER OF THE PLANTER STRIP AND 4" CASING LOCATED UNDERNEATH SIDEWALK.
4. SERVICE LINE INSTALLATION AT AN EXISTING MONOLITHIC CURB, GUTTER & SIDEWALK SHALL HAVE THE UTILITY BOX LOCATED 1-FOOT BEHIND THE SIDEWALK.
5. SERVICE LINE LOCATION FOR AREAS WITH NO CURB, GUTTER & SIDEWALK TO BE DETERMINED BY THE CITY.
6. BEDDING OF PIPE SHALL CONFORM TO HEBER CITY BEDDING STANDARDS FOR CULINARY WATER.

IRRIGATION SERVICE— TWO LOTS

N.T.S

03/12

HEBER CITY
STANDARD DRAWING
IRRIGATION-1A